

Datasheets

Stand II model 6-1/1, 10-1/1 - MobilityLine



Article number

60.31.164

Description

The iCombi Pro oder iCombi Classic 6-1/1 and 10-1/1 is fixed to the MobilityLine base frame II using a mounting kit. Side bars protect the cooking system and together with the large stable castors, they facilitate mobility.



Intended use

This product is only intended for commercial use, such as in restaurant kitchens or catering operations for schools, hospitals, or delis. Any other use runs counter to its intended purpose, and could be dangerous. Any other use runs counter to its intended purpose, and could be dangerous.

Features

- 4 stainless steel castors, Ø 200 mm diameter
- Support with impact protection brackets
- 14 support rails with 62 mm rail distance
- Two-sided opening with side panels and top panel
- Mounting kit for fixing the cooking system on the base frame
- Securing the containers against slipping

Capacity

1/1 GN	Grid	14 x
1/1 GN	20 mm deep	14 x
1/1 GN	40 mm deep	14 x
1/1 GN	65 mm deep	8 x
1/1 GN	100 mm deep	6 x

Use of other containers: 1/3 GN, 1/2 GN, 2/3 GN

Technical specifications

Clearance from floor panel to floor:	180 mm deep
Max. fixed power:	600 kg
Width of racks:	330 mm
Clearance from bottom rack to floor panel:	68 mm

Dimensions and weights

Width (W):	1.199 mm
Height (H):	789 mm
Depth (D):	894 mm
Weight:	84,1 kg

Material

Rust-free stainless steel (CNS 1.4301/AISI 304)

