

Specification/Datasheet

Wall attachment kit model L



Article number

60.78.983

Description

For flush-mounted cooking systems, the wall connection kit ensures a guided steam outlet, a hygienic connection and easy cleaning. The use of the wall connection kit ensures a minimum distance of 1 3/16 in (30 mm) between the iVario and the wall. The wall connection kit is fitted to the rear of the iVario.



Intended use

This product is intended for professional use, such as in restaurant kitchens or catering operations for schools, hospitals, or delis. Any other use runs counter to its intended purpose and could be dangerous. RATIONAL AG assumes no liability for the consequences of improper use.

Features

The wall connection kit can be retrofitted.

Dimensions and weights

Width (W):	40 1/2 in (1,030 mm)
Height (H):	33 1/8 in (840 mm)
Depth (D):	1 1/8 in (30 mm)
Weight:	16.5 lb (7.5 kg)

Special characteristics

When using the wall connection kit, the depth of the cooking system is increased by 30 mm.

The wall connection kit is suitable for the following installation situations:

1. Base unit with substructure and feet
2. Base unit with substructure on plinth
(Please note that the minimum plinth depth increases from 650 mm to 680 mm.)
3. Base unit without substructure on a surface

The wall connection kit cannot be combined with the wall attachment kit.

Material

Stainless steel (CNS 1.4301) + Silikon + EPDM

Equipment/Scope of delivery

The kit consists of a cover frame, and an integrated condensate drain.